


## Technical Data Sheet

D R V CR a R N



### Product Details

<b>Product Code</b>	HW926
<b>Product Range</b>	Venture Plank From Havwoods
<b>Construction</b>	Engineered
<b>Specie</b>	European Oak
<b>Pattern</b>	1-Strip
<b>Process</b>	Sanded & Smoked
<b>Finish</b>	UV Oiled (No further coat required after install)
<b>Profile</b>	Tongue & Groove
<b>Edge Profile</b>	Bevelled Edge
<b>Top Layer</b>	mm Solid European Oak
<b>Backing</b>	Birch Plywood
<b>Thickness</b>	3mm
<b>Width</b>	0mm
<b>Length</b>	Random (Packs may include shorter boards)
<b>Pack Size</b>	2.12-2.60m <sup>2</sup>
<b>Grade</b>	Character
<b>Maintenance</b>	Comprehensive maintenance instructions and materials are available from VidaSpace Ltd. for all products.
<b>Warranty</b>	Speak to a team member

### Installation Methods

<b>Fully Bonded</b>	Yes * (Recommended)
<b>Nailed</b>	No
<b>Floated on Underlay</b>	Yes*
<b>Over Underfloor Heating</b>	Yes *# (Please see our underfloor heating guidelines)

### Grading Criteria

Typically, character grade will include both heartwood and sapwood and allows a wider range of colour variation. Knots are larger and you should expect checks (cracks across the growth ring). Filler will be used, the colour of which is carefully selected to complement the wood rather than to match it exactly, and it may vary from batch to batch.

NB: The product grading criteria is an approximation. Please ask for details

### Technical Criteria

<b>Origin</b>	Europe
<b>Responsible Certification</b>	Cradle to Cradle Certified Bronze
<b>Janka Hardness Rating</b>	1,120 lbf (4,980N)
<b>Formaldehyde Emission</b>	E1 (EN717-1)
<b>Pentachlorophenol Emission</b>	< 5 ppm (CEN/TR 14823)
<b>Slip Testing</b>	65/39 PTV (BS 7976-2:2002+A1:2013)
<b>Reaction to fire (CRF)</b>	3.3kW/m <sup>2</sup>
<b>Thermal Conductivity</b>	λ 0.17 W/m K (EN 12664)